

Filtration Separation Purification

PRODUCT DATA SHEET

Ecosorb® S-406

Ecosorb® S-406 is a moist, non-dusting, multi-functional purification media that combines adsorption, filtration and ion exchange capacity into a single product. Ecosorb® products utilize a proprietary method to affix fine particles of activated carbon and ion exchange resin onto an inert support. By combining the superior kinetics of fine particles with excellent flow characteristics, purification processes run longer and deliver better quality effluents than with standard treatment methods.

S-406 is recommended for decolorization and for the elimination of objectional taste and odor compounds from a variety of food and beverage products. Typical applications include sugar processing, sugar alcohols, starch derived sweetners and artifical sweeteners.

Ecosorb® S-406 can be used either in a traditional slurry (batch or continuous) mode or as a precoat. Depending on the application, 200 to 500% increases in filter cycle throughput and 50 to 90% reductions in solid waste are typical compared to traditional PAC (powdered activated carbon) treatment.

Ecosorb® S-406 is also available as S-406RB, a heat treated version with reduced bioburden (yeast, mold, and bacteria).

Typical Properties

Appearance: Moist powder aggregates

Color: Predominately dark grey to black with some white flecks

Functional Components: Powdered Activated Carbon

Anion Exchange Resin (Chloride Form)

Cellulose Fiber

pH: 6.0 - 8.0Total Moisture: $60 \pm 3\%$

Shelf Life: S-406 – Two Years from Date of Manufacture

S-406RB – One Year from Date of Manufacture

Packaging: Available in 30 lbs/bag; 40 bags per pallet

Ecosorb S-series raw materials comply with applicable food contact requirements

Ecosorb S-series products are Certified as Kosher and Pareve

Ecosorb S-series products are HALAL certified

For more information on Ecosorb® Multi-functional Adsorbent Media contact:

Graver Technologies Customer Service: 1-800-533-6623 Outside the US: 1-302-731-3516 Fax: 1-302-369-8396

Technical Support: 1-800-249-1990
Outside the US: 1-302-731-1700
E-mail us at info@gravertech.com
DE 19702 USA

www.gravertech.com

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or appearance tregulations.